

ITEM 10202.99 M - PAVEMENT EXCAVATION

DESCRIPTION

The Contractor shall remove and dispose of existing pavement as indicated on the plans or as ordered by the Engineer.

MATERIALS

Not specified.

CONSTRUCTION DETAILS

The Contractor shall remove the pavement in a neat workmanlike manner by any suitable means that does not damage the adjacent pavement or existing underground utilities. Sawing to neat lines will be required before the removal of concrete pavement. This work must conform to the details shown on the plans. The removed concrete shall be properly disposed of by the Contractor, off the right-of-way as approved by the Engineer.

METHOD OF MEASUREMENT

Pavement Excavation shall be measured by the number of square meters of pavement removed and disposed of as shown on the plans or ordered by the Engineer.

BASIS OF PAYMENT

The unit price bid per square meter for this item shall include the cost of furnishing all labor, materials and equipment necessary to remove and dispose of the pavement, mesh reinforcement, transverse joints and longitudinal ties except that saw cutting will be paid for under the appropriate item.

Payment shall be the same regardless of whether the entire thickness of pavement is removed or simply the top surface of pavement is removed to provide a transition for resurfacing.

This Specification has been Disapproved as a result of an e-mail from Region 10

Item 10202.9901 should be used in its place

9/11/2000