

ITEM 10203.5101 M - TRIMMING AND RESHAPING ROADSIDE TURF AREAS

DESCRIPTION

The Contractor shall grade and reshape existing roadside turf areas to the lines and grades shown on the plans or as ordered by the Engineer. The work shall include grading of existing turf shoulder and other areas, removal and disposal of any excess material or placement of additional material to provide a satisfactory transverse cross-slope of the turfed roadside area.

MATERIALS

Material required to meet the grade as shown on the plans shall be "Topsoil" in conformance with the provisions of Subsection 613-2.

CONSTRUCTION DETAILS

Material removed shall be disposed of in conformance with the provisions of Subsection 203-3.08 - Disposal of Surplus Excavated Materials.

The reshaping shall include the placement and grading of topsoil to eliminate irregularities between the existing ground and the finished grade. The Contractor shall exercise due care to protect all trees, fences, markers, culverts, underground structures, utilities and appurtenances within and adjacent to the work area. The Contractor shall replace in kind any facilities damaged by his operations at no cost to the State.

The width of this reshaping shall be as indicated in the plans.

METHOD OF MEASUREMENT

This work will be measured as the number of meters of turfed roadside area reshaped, measured along the edge of pavement or shoulder immediately adjacent to the work. The Engineer will determine the locations where this work is not required.

BASIS OF PAYMENT

The unit price bid per meter of this work shall include the cost of furnishing all labor, equipment and materials necessary to satisfactorily complete the work, except for the following:

- A. Seeding and related work will be paid for under the contract item for Establishing Turf.