

**ITEM 06520.51 M - SAWCUTTING EXISTING CONCRETE GRANITE AND ASPHALT CURBS**

**DESCRIPTION**

Under this item the Contractor shall sawcut existing concrete asphalt or granite as shown on the plans or as directed by the Engineer.

**MATERIALS** (Not Specified)

**CONSTRUCTION DETAILS**

An approved power saw shall be utilized to cut curbs to the configuration and depth as specified in the contract documents or as directed by the Engineer. Unless otherwise noted, the depth of the sawcut shall be for the full existing depth of the material being sawed.

Sawcutting for curb removal shall be along a neat line as shown in the contract documents or as directed by the Engineer. After the curb has been cut to its full depth, the Contractor may use pry bars or other methods approved by the Engineer to pry loose the material to be removed.

Care shall be taken not to disturb or damage existing pavement, sidewalk or curbs scheduled to remain.

Any existing pavement, sidewalks and curbs to remain which are damaged through the Contractor's negligence shall be repaired by the Contractor to the satisfaction of the Engineer at no cost to the State.

**METHOD OF MEASUREMENT:**

This work shall be measured by the number of linear meters of sawcutting completed in accordance with the plans, typical sections and as ordered by the Engineer.

**BASIS OF PAYMENT:**

The unit price bid per linear meter of sawcutting shall include the cost of all labor, materials and equipment necessary to complete the work, the removal and disposal of the cut curb, and the cost of any repairs made necessary by damage from the Contractor's operations.