

ITEM 01555.0195 M - CONCRETE STENCILING

DESCRIPTION

Under this item, the Contractor shall stencil areas as shown in the contract documents or as directed by the Engineer.

MATERIALS

As indicated in the contract documents.

CONSTRUCTION DETAILS

The contractor shall submit manufacturer's catalog data, detail sheets of the dimensioned layout of the artwork, and printed instructions, color keys, a job site mock-up for color and texture, and other details as indicated in the contract documents to the Engineer-in-Charge for approval prior to beginning work.

All concrete surfaces to be stenciled shall be pressure washed until all surface contamination has been completely removed.

The stenciling shall be at the locations shown in the contract documents.

Sufficient masking shall be used to ensure that the stenciling products are applied only where specified. Coverage rates shall be monitored to ensure adequate build is achieved.

A protective sealer shall be applied after the stenciling in accordance to the manufacturer's instructions and requirements.

METHOD OF MEASUREMENT

The quantity of stenciling to be paid for under this item will be measured by the number of square meters of stenciling satisfactorily applied as indicated in the contract documents or as directed by the Engineer.

BASIS OF PAYMENT

The unit price bid per square meter of stenciling will include the cost of all labor, materials, tools, and equipment necessary to satisfactorily complete the work.