

ITEM 11559.9001 M - ANTI-GRAFFITI PROTECTION COATING

DESCRIPTION. The work shall consist of the application of Anti-Graffiti Protection Coating to the concrete, brick or stone masonry surfaces indicated on the Contract Plans and where directed by the Engineer.

MATERIALS.

One of the following three products shall be used, as approved by the Engineer for the applicable surface:

1. Knight and Shield-100, as manufactured by East Coast Clean-up Corp., 799 Broadway, NY 10003, Tel. (212) 875-9044.
2. Protect Epoxy, as manufactured by A.G.P. Systems, Inc., Windham, NY 12496, Tel. (518) 734-5880.
3. Graffiti Control, as manufactured by Prosoco, Inc., 111 Snyder Road, S. Plainfield, NJ 07080, Tel. (908) 754-4410.

or, an approved equal.

CONSTRUCTION DETAILS.

1. Prior to application of the Anti-Graffiti Protection Coating, the surfaces to be coated shall be clean, dry and free of dirt, oil and contaminants and meet the approval of the Engineer.
2. The Anti-Graffiti Protection Coating shall be applied to the surfaces in accordance with the manufacturer's instruction and recommendations and shall meet the approval of the Engineer. The Contractor shall supply the instructions to the Engineer at least two (2) weeks prior to starting work. The Contractor shall provide protection to collect anti-graffiti protection coating material to prevent the material from falling onto all areas below the work area.

METHOD OF MEASUREMENT.

The Anti-Graffiti Protection Coating shall be measured per square meter of area coated. Measurement shall be taken as the vertical plans projection for the coated area.

BASIS OF PAYMENT.

The unit price bid for this item shall include the cost of all labor, materials and equipment necessary to complete this work.

No payment will be made for repair of, or replacement of, damaged material, which was made necessary due to the Contractor's operations.