

ITEM 10559.9020 M - TEMPORARY GRAFFITI COVER

DESCRIPTION

Work under this item will be to cover the graffiti A.C.B.H. within the stated 72 hour time limitation using regular business days. This item will be only used when the proper method of elimination can not be used or as directed by the Engineer. Wood surfaces shall not be painted under this item.

This work shall consist of painting over graffiti. The Contractor shall paint over all graffiti on any surfaces within limits in the contract documents. In addition, the Engineer may order that certain graffiti be removed from other types of surfaces.

MATERIALS

All paint used on any surface shall meet the following requirements:

A flat finish acrylic or alkyd primer paint shall be used that must adhere well to the surface and resist fading and chalking.

The paint shall comply with the volatile organic compound (VOC) requirements of New York State Department of Environmental Conservation regulation 6NYCRR Part 205, Architectural Surface Coatings.

The Paint shall be a gray color to the satisfaction of the Engineer.

All materials are to be approved by the Engineer before any work can begin.

CONSTRUCTION DETAILS

The surfaces shall be thoroughly cleaned before painting. All dust, dirt, oil, grease, and other substances which might prevent the adhesion of the paint to the surface shall be removed. No sandblasting will be allowed. Paint shall be applied as soon as practicable after cleaning is completed. If in the opinion of the Engineer, the surface has become soiled, or otherwise contaminated, prior to the application of the paint, the surface shall be re-cleaned at

 no additional cost to the State. The paint shall be applied evenly in a neat and workmanlike manner by a roller or other suitable method, as approved by the Engineer. The rolling shall be done at such a pace that no spinning of the roller or throwing off of paint occurs when the roller is lifted from the surface. The paint shall be feathered out by using light pressure at the end of the stroke to promote uniformity. The graffitied surface shall be painted in small rectangular patterns in order to minimize the area painted and ensure that the graffiti will no longer be "readable" when the painting is complete.

The graffiti on the surface must be completely hidden before the painted area will be measured for payment. The Contractor will be required to repaint areas if the graffiti remains visible after painting at no additional cost to the State. New graffiti at the same location will be measured for payment when the painting meets the requirements of this specification.

ITEM 10559.9020 M - TEMPORARY GRAFFITI COVER

All work must conform to the OSHA standards referred to in subsection 107-05 of the Standard Specifications.

The Contractor will return to the site to completely and permanently eliminate the graffiti with a proper method within 72 hours of suitable atmospheric conditions or A.O.B.E.

METHOD OF MEASUREMENT

This work will be measured by the number of square meters of surfaces painted, in accordance with this specification. Graffiti that is not painted over in accordance with this specification within the time limits specified above will not be measured for payment and no other areas will be measured for payment until the graffiti is painted over.

BASIS OF PAYMENT

To receive payment the Contractor is required to perform and complete the work of painting over the graffiti, within 72 hours using regular business days after receiving the Prompt Initial Response to Graffiti Situations work order by FAX or in writing from the Engineer.

The unit price bid per square meter shall include the cost of furnishing all labor, materials and equipment necessary to complete the work.

There will be no payment for covering ~~or eliminating~~ graffiti that is not done within the time limitations stated in ITEM 10559.9010 M - PROMPT INITIAL RESPONSE TO GRAFFITI SITUATIONS.

ITEM 10559.9020 M - TEMPORARY GRAFFITI COVER

WordPerfect Document Compare Summary

Original document: T:\Documents & Resources\Special Specifications\BYREGION\10\10559902.000

Revised document: C:\TEMP\GWViewer\105599020.wpd

Deletions are shown with the following attributes and color:

~~Strikeout~~, Blue RGB(0,0,255).

Deleted text is shown as full text.

Insertions are shown with the following attributes and color:

Double Underline, Redline, Red RGB(255,0,0).

The document was marked with 8 Deletions, 9 Insertions, 0 Moves.

**This
Specification
has been
replaced by a
version dated
5/9/02**

ITEM 10559.9020 M - TEMPORARY GRAFFITI COVER

--- Revision List ---

Location is Old Page:Old Paragraph New Page:New Paragraph.
Paragraph numbers shown as zero refer to the part of a paragraph that is carried over from the previous page.
The {Hrt/Hpg/Tab/Spc} codes are generic symbols which refer to categories of end-of-line, tab/indent, or space codes.

**This
Specification
has been
replaced by a
version dated
5/9/02**

- 1:2 1:2 Insert using regular business da...
- 1:8 1:8 Change {Tab}6NYCRR -To- {Tab}{Tab}6NYCRR
- 1:9 1:9 Change the{Tab}satisfaction -To- the satisfaction
- 1:12 1:12 Change at{Hrt}no -To- at no
- 1:13 1:12 Change workmanlike{Hrt}manner -To- workmanlike manner
- 1:14 1:12 Change of{Hrt}the -To- of the
- 1:15 1:12 Change rectangular{Hrt}{Bld} -To- rectangular {Bld}
- 2 : 1 1 : 1 3 C h a n g e { H r t } A l l - T o -
{Hrt}{Tab}{Tab}{Tab}{Tab}{Tab}{Tab}{Tab}{Tab}{Tab}{Tab}{Hrt}All
- 2:3 2:3 Change {Hrt}{Hrt}{Und} -To- {Hrt}{Und}
- 2:5 2:5 Change {Hrt}{Hrt}{Und} -To- {Hrt}{Und}
- 2:6 2:6 Insert using regular business da...
- 2:8 2:8 Change covering or eliminating g... -To- covering graffiti