

## **ITEM 11607.36 M - MAINTENANCE REPAIR OF CHAIN LINK FENCING**

### **DESCRIPTION:**

Under this item, the Contractor shall repair or replace damaged chain link fencing at locations shown in the work orders, and as directed by the Engineer.

### **MATERIALS:**

All replacement material shall conform to the requirements specified in Subsection 607-2 of the Standard Specifications.

### **CONSTRUCTION DETAILS:**

The damaged fence shall be restored in kind.

Portions of the damaged fence that are in useable condition, as determined by the Engineer, may be incorporated into the repair.

Bent Posts shall be straightened, or the existing post cut and a new post sleeved onto a 150 mm stub. Where a new post on a new foundation is required, it shall be installed under a separate item.

Damaged Portions of the fence not reused in the repair and other excess material shall become the property of the Contractor, and removed from the job site.

### **METHOD OF MEASUREMENT:**

This work will be measured as the number of Linear Meters of fence repaired in accordance with the specifications, and to the satisfaction of the Engineer. Measurement will be taken between the center lines of the last undisturbed posts.

### **BASIS OF PAYMENT:**

The unit price bid per Linear Meter for the above work shall include the cost of all labor, equipment and materials necessary to complete the work, except that replacement of fence posts with new concrete footings, will be paid separately.