

**ITEM 10607.361913 M - REPLACE CHAIN LINK FENCE FABRIC - 1830 mm HIGH**  
**ITEM 10607.361914 M - REPLACE CHAIN LINK FENCE FABRIC - 1220 mm HIGH**  
**ITEM 10607.361915 M - REPLACE CHAIN LINK FENCE FABRIC - 4880 mm HIGH**  
**ITEM 10607.361916 M - REPLACE CHAIN LINK FENCE FABRIC - 3660 mm HIGH**

**DESCRIPTION**

This work shall consist of replacing steel chain link fence fabric where indicated in the plans and standard sheets and where directed by the Engineer.

**MATERIALS**

Fence fabric shall conform to the requirements specified in the following subsections of Section 700-Materials:

Galvanized Steel Fence Fabric	710-02
Aluminum Coated Steel Fence Fabric	710-04

The type of fence fabric material shall be as indicated in the plans. If the plans do not indicate a type of material, the fabric shall be the same type as existing fence fabric on adjacent sections of fence.

Fabric ties shall be 9 Gage (3.76 mm Nominal Coated Wire Diameter) aluminum coated steel wire or galvanized steel wire, at the Contractor's option. Other necessary hardware shall conform to subsection 607-2 of the Standard Specifications and as indicated in the plans, except that aluminum alloy fittings shall not be used.

**CONSTRUCTION DETAILS**

The provisions of Subsections 607-3.01, 607-3.02, and 607-3.03, shall apply except for the following:

The Contractor shall carefully detach the damaged fence fabric from the existing chain link fence in locations shown on plans or as ordered by the Engineer. Removed fabric shall be disposed of outside the contract site.

The fence fabric shall be attached to line posts with tie wires spaced at a maximum of 350 mm. The tie wires shall be installed in accordance with the special note "Fence Fabric Tie Wires" which is included elsewhere in the proposal. Minor damage to the coating on the tie wire, caused by cutting and twisting operations, will be acceptable as determined by the Engineer.

The fabric shall be secured to all end, corner, pull, and gate posts with stretcher bares fastened to the posts with stretcher bands spaced at a maximum of 350 mm. When the installation of the fencing is completed, the threads of the bolts in the stretcher bands shall be damaged, as directed by the Engineer, to prevent removal of the bolts.

Work necessary to remove damaged fabric and weave new fabric to existing fabric is included in this item. Existing undamaged hardware may be reused as ordered by the Engineer.

**METHOD OF MEASUREMENT**

This work will be measured as the actual number of linear meters, measured to the nearest 0.1 m of Chain Link Fence Fabric, measured along the center line of the fabric satisfactorily installed, in accordance with the requirements of the plans, specifications, standard sheets, and orders of the Engineer.

**BASIS OF PAYMENT**

The unit price bid for Chain Link Fence Fabric shall include the cost of all labor, materials, tools, and equipment necessary to satisfactorily complete the work; and shall include the removal of damaged fabric, hardware, new fabric, and all other necessary materials.