

**ITEM 607.52 06 - REPAIRING RIGHT-OF-WAY FENCE**

**DESCRIPTION**

Under this item the Contractor shall repair existing right-of-way fence at the locations indicated in the contract documents or where directed by the Engineer.

**MATERIALS**

All new material required for this work shall meet the requirements of §607 & §710-30 of the Standard Specifications

Existing material salvaged from the contract may be reused if approved by the Engineer.

Concrete shall meet the requirement of §607-2.01, Portland Cement Concrete for Bases.

**CONSTRUCTION DETAILS**

All the provisions of §607-3.01 & 607-3.06 of the Standard Specifications shall apply.

This work may include installing posts in earth or concrete footings, installing fabric, bracing and hardware.

Posts which are unsuitable for reuse shall be removed along with their footings and the resulting holes shall be backfilled with suitable material to meet the existing grade.

All material removed and not reused shall become the property of the Contractor and shall be removed by him from the contract site.

**METHOD OF MEASUREMENT**

This work shall be measured as the number of meters of fence repaired measured along the top of the fencing from center to center of the posts, properly furnished and installed in accordance with the plans, specifications, standard sheets and directions of the Engineer.

**BASIS OF PAYMENT**

The unit price bid per meter for repairing existing right-of-way fence shall include the cost of furnishing all labor, materials, tools, and equipment including any clearing or grubbing necessary to complete the work..