

ITEM 11607.6301 M - REPAIRING FENCE USING SALVAGED MATERIAL
ITEM 11607.6302 M - REMOVING AND REPLACING DAMAGED FENCE
USING NEW MATERIAL

DESCRIPTION:

The Contractor shall remove, dispose and repair or replace any damaged chain link fence in accordance with the plans, specifications and orders of the Engineer.

MATERIALS:

Fencing hardware shall conform to the requirements of Subsections 710-02 and 710-10.03. Portland Cement Concrete used for bases shall be Class A or C, conforming to the requirements of Section 501 Portland Cement Concrete - General, except that requirements for automated batching shall not apply.

CONSTRUCTION DETAILS:

The damaged sections of fence post and fabric shall be repaired using existing materials, if they can be salvaged.

If the fence is damaged beyond repair, the Contractor shall remove and dispose of any damaged fence when it occurs, and to the extent as directed by the Engineer. This shall include, but is not limited to, the removal of the fence post footings and backfill with suitable material. All fences removed from the site shall be replaced in kind by the same type and size of fencing.

Parts salvaged from the removal portion, acceptable to the Engineer, may be reused. Additional hardware as required to replace the damaged fencing shall be furnished by the Contractor. The integrity of the fence and the function it was intended to serve shall be preserved at all times.

METHOD OF MEASUREMENT:

This work will be measured by the actual number of meters of fence measured along the top of the fence, to be repaired with salvaged material, or removed and replaced by the Contractor.

No payment will be made for repairing items to be stored which are damaged by the Contractor's operations.

BASIS OF PAYMENT:

The unit price bid per meter for the above work shall include the cost of all labor, equipment and materials necessary to complete the work, including the cost of any fill required to fill the post holes.