

**ITEM 10608.0125 M - CONCRETE DRIVEWAYS - CLASS F
(GRADING INCLUDED)**

DESCRIPTION. The work shall consist of the construction of portland cement concrete driveways and necessary grading as shown on the plans.

MATERIALS. The requirements of Subsection 203-2.02A of the Standard Specifications shall apply.

Subsection 608-2 shall apply, except that the portland cement concrete shall comply with the specifications for Class "F" concrete in Subsection 501-2 under "Portland Cement Concrete-General." Concrete shall be proportioned in accordance with the aggregate weights specified for Class "F" concrete in Table 501-3, Concrete Proportions.

CONSTRUCTION DETAILS. The requirements of Subsection 203-3.12 shall apply to the placement of embankment.

Subsection 608-3.01 shall apply except the curing period shall be two days when placement is made between June 1 and September 15 and three days at all other times.

The location of the driveways shall be properly graded to conform with the driveway cross-section and line and grade. The graded area shall be firm and dry before placing the concrete and all organic or unstable materials, existing curbs, sidewalks, and driveways shall be removed.

METHOD OF MEASUREMENT. This work will be measured by the number of cubic meters of cement concrete computed from payment lines shown on the plans.

BASIS OF PAYMENT. The unit price bid per cubic meter shall include all excavation, embankment, preparation of subgrade, wire fabric for reinforcement, and all other materials, equipment, and labor necessary to complete the work as called for on the plans and to the satisfaction of the Engineer.

No separate payment will be made for excavation or embankment above, below, or within the volume of driveway placed.

Payment at the unit bid price will be made after the concrete driveways have been completed and opened to traffic.