

**ITEM 63608.0201 M - ASPHALT CONCRETE DRIVEWAYS, GUTTERS, BICYCLE PATHS AND
SIDEWALKS, EMERGENCY STANDBY READINESS CONTRACT**
ITEM 63608.020111 M - PLANT PRODUCTION QUALITY ADJUSTMENT FOR ITEM 63608.0201M

DESCRIPTION:

This work shall consist of the construction of asphalt concrete driveways, gutters, bicycle paths and sidewalks in accordance to the Standard Specifications and in reasonable conformity with lines and grades shown on the plans or established by the Engineer. This work shall be handwork except where paving machines are specifically approved by the Engineer.

MATERIALS:

All materials used shall meet the respective provisions of Section 700, Materials Details, of the Standard Specifications.

1. Asphalt Concrete Driveways, Bicycle Paths and Sidewalks. The construction shall incorporate one or more of the following types of asphalt concrete:

- Type 1 Base Course
- Type 3 Binder Course
- Type 6 Top Course
- Type 7 Top Course

Mix composition shall be as given in Table 401-1, Composition of Bituminous Plant Mixtures under Subsection 401-2.02. The number of courses and course thickness shall be as given in Table 608-1, Asphalt Concrete Composition, of Subsection 608-2.02 of the Standard Specifications. The following notes shall also apply:

- a. Top Course shall not be applied directly to Type 1 Base Course.
 - b. The surface course shall be Type 6 or Type 7.
 - c. On two course applications, except Commercial Driveways, where Type 3 Binder is called for in thickness of 40 mm or 50 mm Type 6 Top Course layer may be substituted for the Type 3 Binder Course.
 - d. A course shall consist of one or more separate lifts of asphalt concrete, as directed by the Engineer, to attain the indicated thickness.
 - e. Type 6F mix may be used in lieu of Type 6 mix, and Type 7F may be used in lieu of Type 7 mix.
2. Asphalt Concrete Gutters. All provisions of Subsection 624-2.01 shall apply.

CONSTRUCTION DETAILS:

1. Asphalt Concrete Driveways Bicycle Paths and Sidewalks. The provisions under Subsection 401-3, Construction Details for Plant Mix Pavements General, shall apply. The sidewalks and driveways shall be constructed to the depth and dimensions indicated in the Contract Documents, or where directed by the Engineer.
2. Asphalt Concrete Gutters. All provisions of Subsection 624-3.01 shall apply.

**ITEM 63608.0201 M - ASPHALT CONCRETE DRIVEWAYS, GUTTERS, BICYCLE PATHS AND
SIDEWALKS, EMERGENCY STANDBY READINESS CONTRACT**
ITEM 63608.020111 M - PLANT PRODUCTION QUALITY ADJUSTMENT FOR ITEM 63608.0201M

METHOD OF MEASUREMENT:

Asphalt concrete driveways, gutters, bicycle paths and sidewalks will be measured by the number of metric tons of asphalt concrete furnished and incorporated in the work.

BASIS OF PAYMENT:

The unit price per metric ton shall include the cost of preparing the subgrade, all material and equipment and labor necessary to complete the work as specified except that necessary excavation and subbase course will be paid for under their appropriate items.

DISAPPROVED