

## **ITEM 08608.9304 M - IMPRINTED AND TEXTURED CONCRETE**

### **DESCRIPTION:**

Under this item, the contractor shall imprint the surface of concrete with a pattern as directed and/or as shown on the plans. The pattern must be approved by the Engineer-In-Charge.

### **MATERIALS:**

Bomacron Release Agent and Bomanite Sealer - The sealer shall be as distributed by Bomanite of New York (800-972-0668) or approved equal.

### **CONSTRUCTION DETAILS:**

While the concrete is still in the plastic stage of set, the imprinting tools shall be applied to make the desired impression to the surface. Impressions shall not be deeper than 10 mm.

The surface shall be scored by means of a tool or may be saw cut. The depth of score shall be 25 mm. If the saw cut option is used, the saw cutting must be performed later the same day. The surface shall be sealed with two coats of bomanite sealer and curing procedures shall meet the requirements of 502-3.01, Curing.

Quality Assurance - The contractor shall show evidence of successful completion of similar installations. Prior to the start of work, the contractor shall provide a job site sample for the approval of the Engineer. The sample shall be: 4 meters x 2 meters, minimum, constructed at a location selected by the Engineer; not be incorporated into the work; and removed when ordered by the Engineer.

### **METHOD OF MEASUREMENT:**

This work will be measured as the number of square meters of imprinted concrete installed in accordance with the plans, specifications and as ordered by the Engineer.

### **BASIS OF PAYMENT:**

The unit price bid per square meter shall include the cost of furnishing all labor, materials and equipment necessary to complete the work, including constructing and removing the job site sample.