

ITEM 10609.0410 M - CAST-IN-PLACE CONCRETE CURB (GRADING INCLUDED) TYPE A

DESCRIPTION

The work shall consist of the construction of concrete curb or curb and gutter and necessary grading as shown on the plans or as specified by the Engineer.

MATERIALS

The requirements of Subsection 609-2 shall apply. The curb or curb and gutter shall conform to the dimensions shown on the plans.

CONSTRUCTION DETAILS

The requirements of Subsection 609-3.01 and 609-3.04 shall apply.

The location of the concrete curb and gutter shall be properly graded to conform to the curb line and grade. The graded area shall be firm and dry before placing concrete and all organic or unstable materials, existing curbs, sidewalks, and driveways shall be removed.

METHOD OF MEASUREMENT

Concrete curb or curb and gutter placed under this specification will be measured by the number of linear meters, measured to the nearest meter. The measurement will be taken along the top front arris line of the curb or curb and gutter.

BASIS OF PAYMENT

The unit price bid per meter shall include all excavation, embankment, preparation of subgrade, curb anchors, and all other materials, equipment and labor necessary to complete the work as called for on the plans or as specified by the Engineer. The unit price bid shall also include: replacement of curb and curb and gutter that was produced out of tolerance; cleaning of curb or curb and gutter found to be dirty prior to final acceptance; and repair or replacement of curb or curb and gutter damaged by the Contractor's operations.

No separate payment will be made for excavation or embankment above, below, or within the volume of curb placed.