

ITEM 07615.50 M - MONUMENT RELOCATION

Description

Under this item, the Contractor shall remove, store, relocate and place monuments as shown on the plans or as directed by the Engineer.

Materials

The setting compound shall be Monument Setting Compound. The compound shall be delivered to the project site in the Manufacturer's original labeled container.

Color shall be from the Manufacturer's standard colors which most closely conforms to the colors of the monument stone, as selected by the Engineer.

Construction Details

During removal, storage, relocation, and placement, the Contractor shall protect the monument from damage, discoloration, or staining. Following placement, the Contractor shall protect the monument until completion and acceptance of the contract. Any damage to the monument prior to final acceptance shall be repaired to the satisfaction of the Engineer or the monument replaced at the Contractor's expense.

Unless otherwise approved or recommended in writing the setting compound manufacturer, the compound shall not be installed at temperatures below 7 degrees C or above 29 degrees C.

All surfaces adjacent to the areas where the setting compound is to be applied shall be protected with non-staining removable tape and other approved coverings to prevent soiling or staining from droppings. Prior to compound installation all dirt and other foreign matter shall be removed. The method of cleaning and preparing the work surfaces shall be as recommended by the manufacturer and as approved by the Engineer.

25 mm plastic setting cushions or wedge lead shall be placed approximately 18 mm from each corner of the individual monument components prior to the placement of the next component and installation of the setting compound.

The compound shall be placed to a depth between 6 mm and 13 mm with no voids or gaps permitted. The setting compound shall not be installed on surfaces that contain frost or moisture.

Trim excess compound to present a neat, smoothly finished joint. Provide a slightly concave joint surface, unless otherwise directed by the manufacturer.

ITEM 07615.50 M - MONUMENT RELOCATION

Method of Measurement

The work shall be measured as each monument relocated.

Basis of Payment

The unit price bid shall include the cost of furnishing all labor, materials, and equipment necessary to satisfactorily complete the specified work.

DISAPPROVED
BY EI 12-001