

**ITEM 615.9911 11 M - MOVABLE PLANTER TYPE 1**  
**ITEM 615.9912 11 M - MOVABLE PLANTER TYPE 2**

**DESCRIPTION**

Under this item, the Contractor shall furnish and install movable planters in accordance with the plans and specifications.

**MATERIALS**

Type 1 - Large Planter of size and type/finish shown on the plans

Type 2 - Small Planter of size and type/finish shown on the plans

**CONSTRUCTION DETAILS**

**SHIPPING AND HANDLING:**

Deliver planters to the site in undamaged condition. Store and handle planters and related materials to prevent their deterioration or damage due to moisture, temperature changes, contaminants, corrosion, breakage, chipping or other causes.

Do not use pinch or wrecking bars. Lift with wide belt-type slings where possible. Do not use wire rope or ropes containing tar or other substances that might cause staining. If required to move planters on site, use wood rollers with cushions at the end of the wood slides.

**INSTALLATION:**

It shall be the responsibility of the Contractor to ensure that all subgrades, bases and surfaces to receive planters are clean, level and adequately prepared. The Contractor shall verify finished elevations and field dimensions taken at the job site affecting the work. Field dimensions which are at variance with the drawings are to be brought to the attention of the Engineer.

Clean all surfaces of planters which have become dirty or stained prior to installation. Remove all soil, stains and foreign materials. Clean planters by thoroughly scrubbing surface with fiber brushes followed by a thorough drenching with clean water (do not use ferrous or other metallic brush.). Use only mild cleaning compounds that contain no caustic materials or abrasives.

Patched, chipped, cracked, broken or otherwise defective planters shall not be installed. They shall be replaced with new at the Contractor's expense, and the Engineer shall be notified of any such damaged planters.

Install planters as per the plans and manufacturer's instructions. Installation of crushed stone, filter fabric, topsoil and plants in the planters as shown on the plans shall occur after the planters have been installed in the approved positions.

Clean-up: The planters and surrounding area shall be thoroughly cleaned after the approved installation of the planters (including topsoil and plants). Exposed surfaces shall be gone over and any dirt, stains, splashes or smears and any other encrusted matter carefully removed from the surface. If necessary, the cleaning shall be done with non-ionic detergent and clean water applied

**ITEM 615.9911 11 M - MOVABLE PLANTER TYPE 1**

**ITEM 615.9912 11 M - MOVABLE PLANTER TYPE 2**

vigorously with natural fiber bristle brushes. After cleaning, the planters, pavement and surrounding street furniture shall be drenched with clean water.

**METHOD OF MEASUREMENT**

Planters will be measured by the number of whichever type installed as shown on the plans and to the satisfaction of the Engineer.

**BASIS OF PAYMENT**

The unit price bid for each planter shall include the cost of fabrication, delivery and installation of planters and all equipment, materials and labor necessary to complete the work.

DISAPPROVED BY EI 12-001